

# DESCABEND RTS-20

6,00 mm<sup>2</sup> - 50,00 mm<sup>2</sup>

Round braided earthing connectors

## Application

The DESCABEND round braided earthing connectors are suitable for all kind of electrical connections in cabinets, in low voltage systems in general, as switch connections, in the electroplating, etc..



## Construction

Connectors made of tinned copper wires 0,20 mm solderless pressed tinned copper tube contact areas, holes embossed

## Special Characteristics

The characteristics of these earthing connectors are a high power transmission by compact dimension, a high flexibility, they are extremely resistant to vibrations and oscillations and they can be easily installed as measurement errors can be compensated.

Part Number	Type	Section mm <sup>2</sup>	Hole center distance mm	Hole Ø mm	Mounting paid mm	kg / pce
703530	RTS-20	6,00	150	6,50	3.00	0.010
703534	RTS-20	6,00	200	6,50	3.00	0.013
703572	RTS-20	10,00	150	6,50	4.50	0.021
703576	RTS-20	10,00	200	6,50	4.50	0.025
703580	RTS-20	10,00	250	6,50	4.50	0.030
703584	RTS-20	10,00	300	6,50	4.50	0.032
703615	RTS-20	16,00	150	8,50	6.00	0.030
703619	RTS-20	16,00	200	8,50	6.00	0.036
703623	RTS-20	16,00	250	8,50	6.00	0.045
703627	RTS-20	16,00	300	8,50	6.00	0.055
703635	RTS-20	16,00	400	8,50	6.00	0.070
703643	RTS-20	16,00	500	8,50	6.00	0.080
703657	RTS-20	25,00	150	8,50	8.00	0.045
703661	RTS-20	25,00	200	8,50	8.00	0.055
703665	RTS-20	25,00	250	8,50	8.00	0.072
703669	RTS-20	25,00	300	8,50	8.00	0.085
703677	RTS-20	25,00	400	8,50	8.00	0.120
703685	RTS-20	25,00	500	8,50	8.00	0.140
703700	RTS-20	35,00	150	10,50	9.00	0.060
703704	RTS-20	35,00	200	10,50	9.00	0.080
703708	RTS-20	35,00	250	10,50	9.00	0.100
703712	RTS-20	35,00	300	10,50	9.00	0.120
703720	RTS-20	35,00	400	10,50	9.00	0.160
703728	RTS-20	35,00	500	10,50	9.00	0.200
703742	RTS-20	50,00	150	10,50	10.00	0.100
703746	RTS-20	50,00	200	10,50	10.00	0.120
703750	RTS-20	50,00	250	10,50	10.00	0.150
703754	RTS-20	50,00	300	10,50	10.00	0.180
703762	RTS-20	50,00	400	10,50	10.00	0.230
703770	RTS-20	50,00	500	10,50	10.00	0.280

## Standard packaging

10 pieces