

DESCAFLEX 300 UL-NISPT-1

AWG 20 - AWG 18

Cables PVC 105°C 300 V, flat oval, UL/CSA

Application

Flexible electric cables for use in household appliances as lamps, radios, fans, and in an environment that demands a high temperature resistance, etc..

Construction

Flexible bare copper conductors
Insulation PVC, heat-resistant
Conductor colours:
2-pole black, white
3-pole black, white, green
Conductors in parallel
Sheath PVC black, heat-resistant

Part Number	Type n x AWG	Overall-Ø ca. mm	Copper kg/km	Weight kg/km
222070	2 x 20	2.60 x 4.80	12.00	31.00
222071	3 x 20	2.60 x 7.00	18.00	38.00



Technical Properties

Rated voltage 300 V
Temperature range - 20°C ... + 105°C
Minimum bending radius 15 x cable diameter

Normen / Prüfungen

UL listed: NEC/UL specification No. 62
CSA listed: CSA specification C22.2

Part Number	Type n x AWG	Overall-Ø ca. mm	Copper kg/km	Weight kg/km
222072	2 x 18	2.90 x 5.40	16.60	33.00
222073	3 x 18	2.90 x 7.60	24.90	45.00

Packaging

Spools of 152 m, 305 m or different