

# DESCAFLEX 300 UL-SPT-1

AWG 20 - AWG 18

Cables PVC 105°C 300 V, separable, UL/CSA

## Application

Flexible electric cables for use in household appliances as lamps, radios, fans, and in an environment that demands a high temperature resistance, etc..

## Construction

Flexible bare copper conductors  
Insulation PVC heat-resistant, in parallel, black, separable  
(3-pole cable with green interior insulation)



## Technical Properties

Rated voltage 300 V  
Temperature range - 20°C ... + 105°C  
Minimum bending radius 15 x cable diameter

## Standards / Approvals

UL listed: NEC/UL specification no. 62, SPT-1  
CSA listed: CSA specification C22.2 No.49, SPT-1

| Part Number | Type n x AWG | Overall-Ø ca. mm | Copper kg/km | Weight kg/km |
|-------------|--------------|------------------|--------------|--------------|
| 221900      | 2 x 20       | 2.55 x 4.90      | 12.00        | 21.00        |
| 221901      | 3 x 20       | 2.80 x 7.60      | 18.00        | 35.00        |

| Part Number | Type n x AWG | Overall-Ø ca. mm | Copper kg/km | Weight kg/km |
|-------------|--------------|------------------|--------------|--------------|
| 221902      | 2 x 18       | 2.70 x 5.20      | 16.60        | 31.00        |
| 221903      | 3 x 18       | 2.80 x 7.75      | 24.90        | 42.00        |

## Packaging

Spools of 152 m, 305 m or different